

Solvent Polymeric Vehicle Vinyl with Air Egress Self Adhesive

Description	Print	Applications
Surface: 100mic Polymeric White PVC Film (Glossy & Matte) with Air Egress Glue: White/Black/Grey/Repositionable grey /Repositionable black Liner: Double-sided laminated paper, 140g Features: Offers excellent ink absorption stability, with great image quality performance. Provides good dimensional stability. Featuring an air egress adhesive, ensuring smooth and bubble-free results. Shelf Life Ideal Storage Temperature 70°F (21°C) and 50% relative humidity 2 years from factory	<ul style="list-style-type: none"> > UV > Solvent > Eco-solvent 	<ul style="list-style-type: none"> > Vehicel Wrapping > The car body advertisement > Building, bus, Metro decoration > Billboards,bus station signage > Glass wall and other smooth surface etc

■ Physical properties

ITEM	base material (μm)	Glue (g/m ²)	Liner paper (g/m ²)				
PPVCA-100GAD	100±5	20±5	140±5				

Availabilities	Certificates
----------------	--------------

Plotter roll sizes	0.914、1.07、1.27、1.37、1.524m 36"、42"、50"、54"、60"
--------------------	--

Additional sizes and dimensions on request

Best printing results achieved in a standard climate of 23°C and 50% relative humidity. For problem-free running, always store the product in original packaging and protect it from direct sunlight and moisture. Before using our media, check its suitability on your printer and for your planned application. We can assume no liability resulting from technical changes in printers and/or inks. Changes in the product design due to technical further developments will not be announced in advance.

March 2023, subject to alterations